

MANUFACTURER:

SaverSystems

Richmond, IN 47374

800-860-6327

Fax: 765-935-4999

www.chimneysaver.com

DESCRIPTION

Cre-Away is a four-component powder that safely and effectively modifies glazed or third-degree creosote so that it can be more easily removed by chimney sweeping. First, a reactive agent neutralizes the slightly acidic creosote making it less corrosive to metal components and less flammable. Second, a dehydrator absorbs the oils and moisture contained in some forms of creosote. Third, a combustion inhibitor helps reduce the chance of chimney fires. Finally, a magnesium catalyst helps break down third degree creosote when the flue is heated by normal use.

USES

Cre-Away can be used to modify third-degree creosote by converting it into a more brittle state that has a different expansion/contraction rate than the flue it is attached to. During heating and cooling cycles, the treated creosote loses its adhesive properties so it can be more easily removed. Creosote and soot build-up in fireplaces or wood stove chimneys can be a fire hazard if it is not properly cleaned and maintained. **Not recommended for use with wood stoves having catalytic combustors.**

Note concerning third-degree creosote: The time it takes to chemically modify third-degree creosote with Cre-Away will depend on many variables such as: type of wood, moisture content, burning habits, air flow, flue size and amount of existing buildup. In some cases reaction time is fairly fast, within a week or two. Other more difficult build-up problems may require regular use and multiple cleanings during the heating season to completely modify the existing third-degree creosote.

ADVANTAGES

- Effective on all types of creosote
- Helps prevent chimney fires
- Reduces creosote odors
- Chimneys clean easier and more completely when swept
- Ready to use
- Fast and easy to use

DIRECTIONS FOR USE

16 ounce bottle directions for use: Apply product directly into the chimney, NOT in the fire. Tip the dusting bottle on its side, shake vigorously. Point the nozzle directly into the chimney, in the direction of the air flow. A small fire may be required to create a positive air flow up the chimney. Using both hands, squeeze the bottle hard four to five times, forcing a liberal amount of product directly up into the chimney. Repeat if necessary using approximately one third of the bottle, or until the chimney is thoroughly coated.

For taller chimneys: You may want to also spray the powder down from the top of the chimney to ensure coverage at the top. After Cre-Away is applied, a fire needs to be burned in the appliance to trigger the catalyst in Cre-Away. Continue using Cre-Away each time a new fire is set for approximately one week. Then clean the chimney as normally done. After cleaning, apply another coat of Cre-Away to the chimney. Once a week apply additional coats of Cre-Away to the chimney to help keep it free of glazed creosote.

Note: Chimneys containing excessive amounts of creosote may require treatments more often.

Professional applicator directions for use: Apply product directly into the chimney, NOT in the fire. Fill the applicator with Cre-Away. Make sure there is a positive draft in the chimney. A small fire may need to be lit to create the positive air flow. Attach the applicator to a small air compressor or portable air tank. Make sure the air supply has a regulator on it and that the regulator is set to between 20 - 25 p.s.i. Point the nozzle of the applicator directly into the chimney in the direction of the air flow. Release a liberal amount of Cre-Away directly up into the chimney. Repeat as necessary until the chimney is thoroughly coated.

For taller chimneys: You may also want to spray the powder down from the top of the chimney to ensure coverage at the top. After Cre-Away is applied, a fire needs to be burned in the appliance to trigger the catalyst in Cre-Away. Continue using Cre-Away each time a new fire is set for approximately one week. The best way to do this is to leave a 16 ounce bottle with the homeowner and have them use it before each fire. After approximately one week, clean the chimney as you normally do. After cleaning, apply another coat of Cre-Away to the chimney. Once each week apply additional coats of Cre-Away to the chimney to help keep it free of glazed creosote.

CLEAN UP

Cleaning Spills: Remove stains on hard surfaces with hydrogen peroxide to which is added a few drops of white vinegar. Apply to stains, and then blot up. Rinse textiles with water before product dries.

CAUTIONS

Keep out of reach of children. Contains calcium hydroxide. Avoid contact with eyes. Wear goggles when using this product. May cause irritation or burns to eyes or skin. California Proposition 65: This product crystalline silica, a chemical known to the State of California to cause cancer.

FIRST AID

If inhaled: In all cases of doubt, or when symptoms persist, seek medical advice. Remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER/doctor/physician if you feel unwell.

If swallowed: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

For skin contact: Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention.

For eye contact: Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician. For additional information for this product, consult the Safety Data Sheet available at www.chimneysaver.com.

LIMITED WARRANTY

Our recommendations for use of this product are based upon tests believed to be reliable. Since field conditions vary widely, the user must determine the suitability of the product for the particular use and specific method(s) of application. Due to the fact that SaverSystems has no control over surface preparation and application methods, no guarantee as to results is offered, expressed or implied. SaverSystems warrants this product to be free from manufacturing defects.

SaverSystems' liability shall be limited in all events to supplying enough product to re-treat the specific areas to which defective product was applied. This warranty does not include the cost of labor application. SaverSystems shall not have any other liability including direct, incidental, or consequential damages. Some states do not allow the exclusion of incidental or consequential damages, so this limitation may not apply to you. This warranty gives you specific legal rights. You may also have other rights which vary from state to state.

PACKAGING

Available in 16 oz. bottles and 25 lb. recyclable plastic containers.

TRANSPORT AND HANDLING

Cre-Away is not considered hazardous under Department of Transportation (DOT) regulations. Store in a cool, dry place inaccessible to children and animals.

PHYSICAL PROPERTIES

COLOR Gray
ODOR None to slight
DENSITY 55-58 lb/cu